



# Unified Battery Charger 5 Bay Rack Set (with AC adapter) for CISCO 7921G Wireless IP Phone

Product ID:CI921U5B | Compatibility: zBattery and Cisco 7921G Wireless IP Phone Battery



zAdapter® CI921U5B Battery Multi-Charger Set keeps a fleet of Cisco 7921G Wireless IP Phone battery packs charged for continuous, round-the-clock use. Charges up to FIFTEEN (15) standard/extended Li-Ion batteries or zBatteries.

- The ONLY Battery Multi-Charger for Cisco 7921G Wireless IP Phone battery in the market
- Completed compliance with environment and safety standards
- Charges up to FIFTEEN (15) zBatteries or Cisco 7921G Unified Wireless IP Phone standard/extended battery packs at the same time
- It is part of zCover Unified Power Solutions which allows you to expand or exchange modules with same or different models to meet your need
- Separate LEDs show charge and ready states for each battery slot
- Battery slot has Anti-Reverse Insert Lock to ensure batteries are inserted correctly
- Switches to a trickle charge when battery is full
- Safety first, intelligent battery temperature monitor discontinues charging when battery temperature reaches 113°F (45°C)
- Can be placed on a desk or mounted on the wall to save space(Wall mount kits sold separately)
- Power supply has switchable power cord for different countries
- Unified Multi Charger is part of zCover Unified Modular Docking System. It can be docked into zCover Unified Dock Racks to form a Multi-Charger or customize a mixed Multi-charger with other Unified Desktop Dual Chargers or Unified Multi-battery Chargers.



Fits Cisco 7921G Wireless IP Phone Batteries



The zAdapter® CI921U5B Battery Multi-Charger can be placed on a desktop or mounted on the wall



Product ID:CI921U5B| Compatibility: zBattery and Cisco 7921G Wireless IP Phone Battery

Specifications	
Dimensions (L x W x H)	20in x 7in x 5.5in 508mm x 178mm x 140mm
Weight	3402g; 7.5lbs
Power Supply	INPUT : AC100-240V 50/60Hz 1.50A OUTPUT: DC5.0V 6000mA (each battery slot approximately 600mA)
Operating Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10 to 95% (no condensing)
Charging Time	Use zAdapter power supply: 2.5 hours / 3 hours (standard battery pack / extended battery pack)
What is in the box:	5 x CI921UBK    Unified Multi-Battery Charger for Cisco 7921G Wireless IP Phone 1 x ZDUPSR5K    zAdapter® Unified Dock Rack. FIVE (5) Bays, with no power adapter 1 x ZDP5V6AB    zAdapter® Power Adapter for Multi-port chargers with certified AC Power Cord 1 x ZDADBT(XX) = Power cord with your choice of plug connector XX = AU (Australia), EU (Continental Europe), JP (Japan), NA (North America), UK (United Kingdom) & CN (China)

Part ID Number	Description
CI921U5B-NA=	15 Batteries Multi Charger Set fits Cisco 7921G Wireless IP Phone, with power cord for North America
CI921U5B-AU=	15 Batteries Multi Charger Set fits Cisco 7921G Wireless IP Phone, with power cord for Australia
CI921U5B-JP=	15 Batteries Multi Charger Set fits Cisco 7921G Wireless IP Phone, with power cord for Japan
CI921U5B-UK=	15 Batteries Multi Charger Set fits d81/d62/i62 handset batteries, with power cord for United Kingdom
CI921U5B-EU=	15 Batteries Multi Charger Set fits d81/d62/i62 handset batteries, with power cord for Continental Europe
CI921U5B-CN=	15 Batteries Multi Charger Set fits d81/d62/i62 handset batteries, with power cord for China

## Related zCover Products



zCover, Inc.

Tel: (604)273-3003 Fax: (604)273-3023

PO & Sales Support: sales@zcover.com

100-13551 Verdun Place Richmond, BC,

Canada V6V 1W5

Purchase Online: [www.zcover.com](http://www.zcover.com)

©2012 zCover Inc. All rights reserved. zCover, zBattery and zAdapter are registered trademarks in USA and other countries.  
All other trademarks are the property of their respective owners.