



## Unified Modular Docking System for ASCOM d62/i62 Wireless Handset with Patented Dock-in-Case® Solution

Product ID:AS62AU3A



zAdapter® AS62AU3A Multi-Charger Set for ASCOM d62/i62 Wireless Handset charges up to THREE (3) ASCOM d62/i62 phones and THREE (3) batteries simultaneously.

The Multi-Charger is ideal for handsets used during consecutive, multiple shifts and keeps a fleet of phones and spare batteries charged and ready for continuous, round-the-clock use. The unit can be placed on a desk or mounted on the wall to save space.

- The ONLY Dock-In-Case Multi-Charger for ASCOM d62/i62 Wireless Handset in the market
- Completed compliance with environment and safety standards
- Charges up to THREE (3) phones and THREE (3) spare batteries at the same time
- Designed with patented Dock-in-Case® solution which allows user to charge phones with or without zCover carrying case
- Full access to keypad allows phone to be dialed while it's docking
- Easy to use, monitor phone charging process on phone screen and battery charging process with LED indicators on charger
- Switches to a trickle charge when battery is full
- Safety first, intelligent battery temperature monitor discontinues charging when battery temperature reaches 113° F (45° C)
- Space saving design, store power supply inside Multi-Charger
- Can be placed on a desk or mounted on the wall to save space
- Compatible with zAdapter® Voice Control Bluetooth Speaker Phone
- Unified Multi-Charger is part of zCover Unified Modular Docking System. It can be docked into zCover Unified Dock Racks to form a Multi-Charger or customize a mixed Multi-charger with other Unified Desktop Dual Chargers or Unified Multi-battery Chargers



Independent “smart” charger circuit in each slot



The zAdapter® AS62AU3A Multi-Charger can be placed on a desktop or mounted on the wall

Specifications	
Dimensions (L x W x H)	14in x 7in x 5.5in 356mm x 178mm x 140mm
Weight	2721g; 6 Lbs
Power Supply	INPUT : AC100-240V 50/60Hz 1.50A OUTPUT: DC5.0V 7000mA (each battery slot is approximately 700mA)
Operating Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10 to 95% (no condensing)
Charging Time	Use zAdapter power supply: Spare battery only: 2 hours (standard battery pack) Battery installed in phone (phone powered off): 2 hours (standard battery pack) Battery installed in phone (powered off) and a spare battery: 2 hours (standard battery pack)
What's in the box:	3 x AS62AUAK Unified Desk Top Dual Charger fits ASCOM d62/i62 Wireless Handset 3 x AS62ACUP zAdapter® AS62A Desktop Dual Charger Docking Cup ONLY 1 x ZDUPSR3K zAdapter® Unified Dock Rack. Three (3) Bays, with no power adapter 1 x ZDP5V6AB zAdapter® GM60 5V60W Power Adapter for Multi-Chargers, Certified AC Power Cord 1 x ZDADBT(XX) Power cord with your choice of plug connector XX = AU(Australia), EU (Continental Europe), JP (Japan), NA (North America), UK (United Kingdom) & CN (China)

Part ID Number	Description
AS62AU3A-NA=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for North America
AS62AU3A-AU=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for Australia
AS62AU3A-JP=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for Japan
AS62AU3A-UK=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for United Kingdom
AS62AU3A-EU=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for Continental Europe
AS62AU3A-CN=	3 Phones/3 Batteries Multi Charger fits ASCOM d62/i62 Wireless Handset with power cord for China

## Related zCover Products



zCover, Inc.  
 Tel: (604)273-3003 Fax: (604)273-3023  
 PO & Sales Support: sales@zcover.com  
 100-13551 Verdun Place Richmond, BC,  
 Canada V6V 1W5  
 Purchase Online: www.zcover.com