



Unified Battery Charger 3 Bay Rack Set (with AC adapter) for CISCO 7921G Wireless IP Phone

Product ID:CI921U3B| Compatibility: zBattery and Cisco 7921G Wireless IP Phone Battery



zAdapter® CI921U3B Battery Multi-Charger Set keeps a fleet of Cisco 7921G Wireless IP Phone battery packs charged for continuous, round-the-clock use. Charges up to NINE (9) standard/extended Li-Ion batteries or zBatteries.



Fits Cisco 7921G Wireless IP Phone Batteries

- The ONLY Battery Multi-Charger for Cisco 7921G Wireless IP Phone battery in the market
- Completed compliance with environment and safety standards
- Charges up to NINE (9) zBatteries or Cisco 7921G Unified Wireless IP Phone standard/extended battery packs at the same time
- It is part of zCover Unified Power Solutions which allows you to expand or exchange modules with same or different models to meet your need
- Separate LEDs show charge and ready states for each battery slot
- Battery slot has Anti-Reverse Insert Lock to ensure batteries are inserted correctly
- Switches to a trickle charge when battery is full
- Safety first, intelligent battery temperature monitor discontinues charging when battery temperature reaches 113°F (45°C)
- Can be placed on a desk or mounted on the wall to save space(Wall mount kits sold separately)
- Power supply has switchable power cord for different countries
- Unified Multi Charger is part of zCover Unified Modular Docking System. It can be docked into zCover Unified Dock Racks to form a Multi-Charger or customize a mixed Multi-charger with other Unified Desktop Dual Chargers or Unified Multi-battery Chargers.



It compatible with CISCO 7921G IP Phone standard and extend battery. It charges 3 Battery simultaneously.



The zAdapter® CI921U3B Battery Multi-Charger can be placed on a desktop or mounted on the wall



Product ID:CI921U3B | Compatibility: zBattery and Cisco 7921G Wireless IP Phone Battery

Specifications	
Dimensions (L x W x H)	14in x 7in x 5.5in 356mm x 178mm x 140mm
Weight	2721g; 6lbs
Power Supply	INPUT : AC100-240V 50/60Hz 1.50A OUTPUT: DC5.0V 6000mA (each battery slot approximately 600mA)
Operating Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-22°F to 140°F (-30°C to 60°C)
Relative Humidity	10 to 95% (no condensing)
Charging Time	Use zAdapter power supply: 2.5 hours / 3 hours (standard battery pack / extended battery pack)
What's in the box:	3 x CI921UBK Unified Multi-Battery Charger for Cisco 7921G Wireless IP Phone 1 x ZDUPSR3K zAdapter® Unified Dock Rack. Three (3) Bays, with no power adapter 1 x ZDP5V6AB zAdapter® Power Adapter for Multi-port chargers with certified AC Power Cord 1 x ZDADBT(XX) = Power cord with your choice of plug connector XX = AU (Australia), EU (Continental Europe), JP (Japan), NA (North America), UK (United Kingdom) & CN (China)

Part ID Number	Description
CI921U3B-NA=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for North America
CI921U3B-AU=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for Australia
CI921U3B-JP=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for Japan
CI921U3B-UK=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for United Kingdom
CI921U3B-EU=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for Continental Europe
CI921U3B-CN=	9 Batteries Multi-Battery Charger Set (with AC adapter) for zBattery and Cisco 7921G Wireless IP Phone Batteries, with power cord for China

Related zCover Products

zCover, Inc.
 Tel: (604)273-3003 Fax: (604)273-3023
 PO & Sales Support: sales@zcover.com
 100-13551 Verdun Place Richmond, BC,
 Canada V6V 1W5
 Purchase Online: www.zcover.com